

525 WORKHORSE RENTAL



Flexibility: the Workhorse Trailer features three ways to load water, including hydrant fill self loading and over the top Filling with a quick connect Ad-on Available.

SPRAY A 180 X 220
FT. ARENA
WITHOUT REFILLING



Performance: The Three output options create optimal performance by allowing you to control dust with the rear spray bar, water up to 100 ft. away, or using the side manifold.



Cost Effective: Avoid expensive truck rentals. Quality design eliminates downtime, and easy to maintain design lead many trailers lasting 15+ years.

TOW WITH A HALF
OR THREE-QUARTER
TON PICKUP!

CIEQUIP.COM
520-579-7458



**Arizona Trailer Specialists, Inc.
dba C&I Equipment Co.**

3841 E 38th St. Tucson, AZ 85713 Office – 520.579.7458

Frame Specs:

Axles	Dexter Leaf-Spring 3500LB axles 74" hub face Electric brakes 545 hub/drum
Tires and Wheels	ST205/75D15
Hitch	2" Height Adjustable Bulldog Type Coupler
Jack	5000lb Adjustable Swivel Jack
DOT Approval	LED Recessed Lighting Reflective Stickers Electric Brakes Brake Away System Safety Chain Kit License Plate Mount and Light 5" Steel Channel.
Material	Deck designed specifically for corresponding tank.
Color	Industrial Charcoal Grey (Customizable)
Fenders	Custom Heavy-Duty Diamond Plated
Dimensions	L x W x H, approximately 151" x 80" x 88"
Weight	Approximately 1600lbs unloaded, 5978lbs
Warranty	1 Year Manufacturers Warranty

Tank Specs:

Capacity	525-gallons
Color	Translucent White, or Black
Material	Polyethylene
NSF-61 Approval	Yes
Gallon Indicators	Yes
Inlet	16" threaded, vented manhole. All models include a vented lid, potable lid will also be lockable.
Outlet	2" NPT Bulkhead Fitting
Bands	(2) Support bands will fasten the tank to the trailer
Dimensions	L x W x H, 71" x 49" x 54"
Warranty	3 Year Manufacturers Warranty



Arizona Trailer Specialists, Inc.
dba C&I Equipment Co.

3841 E 38th St. Tucson, AZ 85713 Office – 520.579.7458

Pump Specs:

Standard Pump: Multiquip QP2H	Max. Water Capacity 142 gpm Max. Lift 25 ft Max. Head 115 ft Max. Pressure 49.8 psi Powered by 3.5HP GX120 Honda gasoline engine 1 Year Manufactures Warrenty
-------------------------------	--

Included Features:

Self-Loading (Drafting) Kit	2" Kit Which Includes the 2" x 25' Suction Hose, and Strainer.
Tank Manhole	16" Overhead Fill equipped with lid.
Hydrant Fill Kit	2 ½" Kit Which Includes the 2 ½" x 25' Hydrant hose, and Hydrant Wrench
Dual-Headed Rear-Spray Bar	Galvanized 2" Steel pipe with (2) galvanized silted caps
1" X 100' Coxhose Reel	1" x 100' hose fixated on the hand crank Coxhose reel.
Side Manifold	-1 ½" Camlock discharge connection for the included 1 ½" x 50' fire hose and adjustable fog nozzle -3/4" Hose Bib -Check Valve -2" Control valve for Rear Spray Bar
Hose Box	Fender Mounted Lockable Hose Box: Storage Solution for Hoses and Accessories
Side Spray Attachment	Steel Welded Hose Holder Mounted on the Frame Silted cap attachment to connect to side manifold
Spare Tire + Welded Carrier	Custom welded carrier mounted to the frame with spare tire
Electric Valve	Electric Valve To Control RSB from Towing Vehicle