525 ARENA SPECIAL RENTAL



spray bar provides
water over a large
surface area for dust
control, while the
side manifold
distributes water via
a fire or garden hose
connection.

Performance: The Arena Special/Firefighter Special is optimized for dust suppression and helping put out fires. Allowing ease and efficiency between job sites. expensive truck rentals.

Quality design
eliminates downtime,
and easy to maintain
design lead many
trailers lasting 15+
years.

SPRAY A 180 X 220 FT. ARENA WITHOUT REFILLING

TOW WITH A HALF OR THREE-QUARTER TON PICKUP!

CIEQUIP.COM

520-579-7458



Arizona Trailer Specialists, Inc. dba C&I Equipment Co. 3841 E 38th St. Tucson, AZ 85713 Office – 520.579.7458

Frame Specs:

Deutaglas (Caria - 2500) Daylar
Dexter Leaf-Spring 3500LB axles
74" hub face Electric brakes
545 hub/drum
ST205/75D15
2" Height Adjustable Bulldog Type Coupler
5000lb Adjustable Swivel Jack
LED Recessed Lighting
Reflective Stickers
Electric Brakes
Brake Away System
Safety Chain Kit License Plate Mount and Light 5"
Steel Channel.
Deck designed specifically for
corresponding tank.
Industrial Charcoal Grey (Customizable)
Custom Heavy-Duty Diamond Plated
L x W x H, approximately 151" x 80" x 88"
Approximately 1600lbs unloaded, 5978lbs
1 Year Manufacturers Warranty

Tank Specs:

Capacity	525-gallons
Color	Translucent White, or Black
Material	Polyethylene
NSF-61 Approval	Yes
Gallon Indicators	Yes
Inlet	16" threaded, vented manhole. All models
	include a vented lid, potable lid will also be
	lockable.
Outlet	2" NPT Bulkhead Fitting
Bands	(2) Support bands will fasten the tank to the
	trailer
Dimensions	L x W x H, 71" x 49" x 54"
Warranty	3 Year Manufacturers Warranty



Arizona Trailer Specialists, Inc. dba C&I Equipment Co. 3841 E 38th St. Tucson, AZ 85713 Office – 520.579.7458

Pump Specs:

Standard Pump: Multiquip QP2H	Max. Water Capacity 142 gpm
	Max. Lift 25 ft
	Max. Head 115 ft
	Max. Pressure 49.8 psi
	Powered by 3.5HP GX120 Honda gasoline engine 1 Year Manufactures Warrenty

Included Features:

Tank Manhole	16" Overhead Fill
Dual-Headed Rear-Spray Bar	Galvanized 2" Steel pipe with (2) galvanized slit caps
Side Manifold	1 ½" Camlock discharge connection for the included 1 ½" x 50' fire hose and adjustable fog nozzle -3/4" Hose Bib -Check Valve -2" Control valve for Rear Spray Bar
Hose Holder	A mounted lockable tool box attached to the fender with storage for two hoses.
Hydrant Fill Kit	2 ½" Kit which Includes the 2 ½" x 25' Hydrant Fill hose, and Hydrant Wrench